

# PROMET COMPARISON



|                               | PROMET L10               | PROMET L100s                              | PROMET SE            | PROMET R300          | PROMET R600  |
|-------------------------------|--------------------------|---|----------------------|----------------------|--|
| <b>Measurement technology</b> |                          |   |                      |                      |  |
| Resistance                    | Range                    | up to 5 kΩ                                | up to 2,5 Ω          | up to 250 mΩ         | up to 250 mΩ   |
|                               | Accuracy                 | 0.2 %                                     | 0.2%                 | 0.2 %                | 0.1 %  |
| Current source                | Outputs, Number          | 1   | 1                    | 2                    | 1  |
|                               | Test current, adjustable | 1 mA...10 A                               | 1...100 A            | 5...200 A            | 10...300 A   |
|                               | Measurement time         | -   | adjustable           | -                    | adjustable   |
|                               | Output voltage           | 5 VDC                                     | 10 VDC               | 2.5 VDC              | 5 VDC  |
| Voltage measurement           | Inputs, Number           | 1   | 1                    | 2                    | 3  |
| Inductive measurements        |                          | •   | •                    | -                    | -  |
| Temperature compensation      |                          | •   | •                    | •                    | •  |
| <b>Operation</b>              |                          |   |                      |                      |  |
| Display                       |                          | Graphical-LC-Display,<br>128 x 64 Pixel   | 5"-Touchscreen       | 3,5"-Touchscreen     | 5"-Touchscreen   |
| Internal memory               | Number of measurements   | No internal memory,<br>storage via APP    | 900                  | 250                  | 900  |
| Software                      |                          | APP, iOS/Android                          | Windows-Software     | Windows-Software     | Windows-Software   |
| Remote control                |                          | -   | -                    | -                    | via USB/Ethernet   |
| <b>Design</b>                 |                          |   |                      |                      |  |
| Power supply                  |                          | Battery operation<br>Exchangeable battery | Battery operation    | Mains operation      | Mains operation  |
| Housing                       |                          | Hand-held housing                         | Hard-top case        | Hand-held housing    | 19" housing for rack-mounting, 3 U, optional: portable housing |
| Dimensions                    |                          | (100 x 230 x 35) mm                       | (318 x 152 x 257) mm | (200 x 178 x 100) mm | (483 x 132,5 x 230) mm   |
| Protection class              |                          | IP 31                                     | IP 67                | IP 54                | IP 20  |
| Weight                        |                          | 0.6 kg                                    | 4.5 kg               | 1.5 kg               | 7.6 kg   |
|                               |                          |   |                      |                      | 10.5 kg  |

